

MICC Accessories



STANDARD PLAIN SEALS AND GLANDS

Light Duty Seal Pot Seal **RPS-L--** Gland **RGM-L--**
 Heavy Duty Pot Seal **RPS-H--** Gland **RGM-L--**




STANDARD EARTH TAIL SEALS & GLANDS

Light Duty Pot Seal **RPSL-L--** Gland **RGM-L--**
 Heavy Duty Pot Seal **RPSL-H--** Gland **RGM-H--**



Cable P CLIPS BARE & LOW SMOKE & FUME (LSF)

Pyro P Clips light duty Bare **-L-RC--** LSF **-L-RCHL--**
 Pyro P clips Heavy duty Bare **-H-RC--** LSF **-H-RCHL--**



Cable saddles BARE & LOW SMOKE & FUME (LSF)

MICC Saddles Light duty Bare **-L-RS---** LSF **-L-RSFL---**
 MICC Saddles Heavy duty Bare **-H-RS---** LSF **-H-RSFL---**



ACCESSORIES

LSF Gland Shrouds **RHGMM--** (20, 25, 32, 40mm)

PVC Gland Shrouds **RHG--** (only 20mm)



Pyro Strap Bare Copper (Pre punched) **RSH12** or **RSH18** (5 mtrs in Orange, Red, Black, White)

Pyro Strap Plastic Covered Copper (Pre punched) **RSHL12** or **RSHL18** (5 mtrs in Rd, Or, Bk, Wt)

Pyro Strap Bare Copper (Solid) **RSZ12** or **RSZ18**

Pyro Strap Plastic Covered Copper (Solid) **RSZL12** or **RSZL18**



Brass Locknuts **RLM--** (20,25,32,40)mm



Zinc Plated Steel Lockwashers (**RLWS--** (20,25,32,40)mm

Conductor PVC Insulated Sleeving (Max Temperature 105°C 3 mtrs)

RZP-- (1.5,2.5,4,6,10,16,25,35,50,70,95)mm² Red Yellow Blue Black Yellow/Green

PVC Extension Sleeving (Max Temperature 105°C 3 mtrs) Red Yellow Blue Black Y/G

RZE-- (1.5,2.5,4,6,10,16,25,35,50,70,95,120,150,185,240)mm²



Silicone Elastomer Coated Glass Sleeving (Max temperature 150°C 3 mtrs)

RZPS-- (1.5,2.5,4,6,10,16,25,35,50,70,95,120,150,185,240)mm² and colour

Coloured Sleeving PTFE (Max Temperature 250°C)

RZP-- (1.5,2.5,4,6,10,16,25)mm²

Cable Terminal Lugs - CYTOLOK

RQK-- (16,25,35,50,70,95,120,150,185,240)mm²



Increased Safety Seal - Plain Seals

Light duty **RPA-L--** Heavy duty **RPA-H--**

Increased Safety Seal - Earth Tail

Light duty **RPAL-L--** Heavy duty **RPA-H--**



Straight Through Joint Tube **RJMZ--** (20,25,32,40)mm

Surge Voltage Diverters

2 Terminal General Purpose for use up to 415 volts

RRN 2

3 Terminal General Purpose for use with FHP motors

RRN 3

2 Terminal Heavy Duty for use up to 240 volts

RRN 1

2 Terminal Light Duty for use up to 240 volts

RNN4

Sealing Compound **TRMX** in 166gram packs