



**EX-ISB-**  -  -  -  -  -  -  -  -  -  -  -  -

- 12 **THREAD TYPE**  
B=BSP, N=NPT
- 11 **THREAD SIZE**  
C=1/2"
- 10 **FITTINGS**  
S=SS
- 9 **HEAD TYPE** (Refer Data sheet)  
LB=LH2, LB\*=LH2(Ex d) FOR TB  
LT=LH2, LT\*=LH2(Ex d) FOR TX
- 8 **TYPE**  
2=2-Wire, 3=3-Wire, 4=4-Wire
- 7 **TEMPERATURE RANGE**  
H=>250°C, L=<250°C
- 6 **CALIBRATION**  
A=Pt100-Din
- 5 **No OF ELEMENTS**  
S=Single, D=Duplex
- 4 **SHEATH**  
A=316SS
- 3 **LENGTH 'L'**  
(In mm)
- 2 **DIAMETER**  
3, 6, 8mm
- 1 **SENSOR TYPE**  
R= RTD

Note 1: If RTD is to be used with a thermowell, please nominate  
 Type: \_\_, 'U' Length: \_\_\_\_\_, 'T' Length: \_\_\_\_\_ (Refer Thermowell data sheets)

**SELECTION**

**EXD-ISB -** R -    -    - A -    - A -    -    -    - S -    -     
 1      2      3      4      5      6      7      8      9      10    11    12

**Special Requirements:** \_\_\_\_\_ **Note: ISB/ISE are interchangeable**